

Ultrasonic Heating and Cooling Meter Residential

Landis
Gyr⁺
manage energy better



Ultrasonic Static Meter

ULTRAHEAT/ ULTRACOLD T230

Simply the best:
The new generation of residential heating
and cooling meters with a composite-flow part

Superiority by economic efficiency

Ultrasonic heating and cooling meters, especially the T230, represent a promising alternative to mechanical meters.

Due to their numerous advantages they will substitute the conventional meters in long term.

The T230 offers a host of impressive and convincing technical advancements. For example has the T230 a significantly lower pressure loss, which simplifies the dimensioning of the meter and economizes expensive operating current year by year.

Thus helps to save your money.

Confidence by accuracy

The T230 works with the proven ultrasonic measurement technology of Landis+Gyr giving the highest accuracy, no maintenance and stable measurement for years and years.

Ultrasound measurement of flow is as precise as overloadable, also insensitive to dirt in the heating water and it ensures a smooth operation over time.

This is what we call state-of-the-art technology.

Customer satisfaction

With the huge dynamic range of 1:1000 all flow rates can precisely be measured, even the smallest. The hard-coded starting value amounts only a few liters per hour and isn't be affected by soiling or abrasion. This enables a fair and suitable billing as well as high customer satisfaction.

Ecological efficiency

To meet market requirements, customer satisfaction and environmental friendliness we have used a new durable material in the volume measuring tube for residential meter application.

The robust glass-fiber reinforced tube is very light and makes the meter easy to handle and simplifies the installation.

This saves transportation costs and reduces emissions.

The reduction of batteries with less Lithium protects the environment as well.

Your needs answered with ease

The ULTRAHEAT/COLD®T230 is the new generation of ultrasonic heating or cooling meter especially developed and optimized to meet all residential needs. The meter has impressive features; light in weight, robust, economic efficiency, user-friendliness, and its new individuality. Improved features made for easier handling and understanding.



Performance Features

- Ultrasonic Heating or Cooling meter
- Smart Metering for all applications
- Flat, removable calculator
- Huge and easy readable Display
- Temperature range: 5-90 °C
- Huge dynamic range: 1:1000
- Storage for 24 monthly values
- 2 monthly set days
- Environmental-friendly construction
- Fast and save mounting
- Any mounting orientation without limitation
- glass-fiber reinforced measuring tube - robust and lightweight
- Comply with the strict European directive (class 2)
- Fast communication
- Precise, robust, nonwearing

Technical Data

Approval	MID (EN 1434)	Nominal flow rate	qp (m³/h)	0.6	1.5	2.5
Protection class (flow part)	IP 54/ (IP65)	Max. flow	qs (m³/h)	1.2	3.0	5.0
Display LCD	7-digit	Min. flow	qi (l/h)	6	15	25
Energy units	kWh / MWh or MJ / GJ	Operating limit	(l/h)	1.2	3	5
Temperature range	(C°) 5-90	Mounting length	(mm)	110	110 / 130	130
Nominal pressure	PN (bar) PN16	Thread connection		G¾	G¾ / G1	G1
Max. Diff. of Temp.	(K) 80	Pressure loss at qp (mbar) (mounting length 110)	(mbar)	75	135	--
Min. Diff. of Temp.	(K) 3	Pressure loss at qp (mbar) (mounting length 130)	(mbar)	--	135	165
Switch-off limit	(K) 0.2					

Communication Interface

M-Bus-Interface (option), with 1.5 m cable connected, with galvanic isolation

Norm:	EN 13757-2 and 13757-3
Voltage:	50V max.
Current:	1 M-Bus leads (1.5 mA)
Addressing:	primary or secondary
Permitted mean frequency of reading:	>1 min @ 2400 bd

New use- and helpful features

Modern features simplify the handling of the meter from the installation up to the immediate identification of mounting errors.

The 2 monthly set days for energy, volume and maxima are very helpful at a tenant change. Additional to the established features, such as permanent error detection and resetting of the missing time after first installation etc; additional information like e.g. activity indication and storage of maxima have been added. This creates more plausibility and helps to identify disturbances in systems.

Faster communication

The T230 is equipped as standard with an optical interface according to EN 1434-3, for a faster mobile read out or for the service software UltraAssist.

For the more comfortable remote read out the meter can be ordered with a factory fitted M-Bus-module.

Space is available within the meter for future communication interfaces enabling an upgrade for new standards and technologies, e.g. radio communication.

Removable calculator - individual mounting

The smart calculator is supplied fitted on the measuring tube but may be mounted on the wall (split mounting) to enable ease of reading and it also helps to prevent condensation in the cooling meter. Even the for mechanical meters not allowed over-head mounting is possible without any difficulty.

Whether fitted on the measuring tube or on the wall the calculator can be rotated to make it easier to read the display.

Manage energy better

Landis+Gyr is the leading global provider of integrated energy management products tailored to energy company needs and unique in its ability to deliver true end-to-end advanced metering solutions. Today, the Company offers the broadest portfolio of products and services in the electricity metering industry, and is paving the way for the next generation of smart grid.

Landis+Gyr, an independent growth platform of the Toshiba Corporation (TKY:6502) and 40% owned by the Innovation Network Corporation of Japan, operates in 30 countries across five continents, and employs 5,000 people with the sole mission of helping the world manage energy better.

More information is available at www.landisgyr.com.

Landis+Gyr in short

- 5000 employees worldwide
- Operations on all five continents
- Broadest portfolio of products and services in the industry
- 25 years of smart metering experience
- 1000 AMM systems delivered
- 300 million energy meters produced
- Largest relevant engineering capacity in the industry
- 65 years of direct load management experience
- 25 million load management receivers produced
- ISO certified for quality and environmental processes
- World leader in integrated energy management solutions
- Committed to improved energy efficiency and environmental conservation
- Solid and established partner network

Landis+Gyr AG

Theilerstrasse 1
6301 Zug
Switzerland

Tel. +41 41 935 6000
Fax +41 41 935 6601
info@landisgyr.com

www.landisgyr.eu

Landis+Gyr GmbH

Humboldtstr. 64
D-90459 Nuremberg
Germany

phone: +49 911 723 7036
fax: +49 911 723 7301
info-nbg.de@landisgyr.com